CRV 6002 set

Rear view video set

5,6“ TFT LCD monitor with shutter color-camera

WEITERE INFOS

Features:

- Rear view video set consisting of:
  5,6“ (12,4 cm) LCD-TFT monitor & shutter color-camera
  incl. monitor stand, 20 m connection cable (394-IP)
- Easy to install and stock (plug & play)
- For 12 V & 24 V application

Monitor:

- Rear view monitor with 2 camera inputs
- 7 languages OSD
- High resolution
- 2 individual trigger wires
- Power on at voltage
- Priority adjustable
- Day/night switch

Rear view camera:

- Sturdy color-camera with
  motorized shutter against pollution
- Camera viewing angle: 130°
- Camera protection class: IP69K
- 6 x IR LED residual light amplifiers for
  better performance in dark areas (0 lux)

Special accessories (optional):

- Additional/spare camera DBC 114065S1

Technische Änderungen und Irrtümer vorbehalten.

Axion AG Röntgenstraße 4 D-89264 Weißenhorn PHONE: +49 (0) 7309 / 42 88-0 info@axionag.de **WWW.AXIONAG.DE**

CRV 6002 Set

Rear view video set

5,6“ TFT LCD monitor with shutter color-camera

Technical data:

Monitor

- 5,6" TFT LCD monitor: 4:3
- Wide viewing angle: r/l 65°, u/d 45/65°
- High brightness: 300 cd/m²
- Resolution: 224640 Pixel
- Mirror/normal picture switch available
- Day/night sensor
- Built-in speaker
- Video system: PAL/NTSC (auto)
- Power supply: 12/24 V (+/- 10%)
- Power consumption: < 7 W
- Operating temperature range: -20 °C to + 70 °C
- Storage temperature range: -30 °C to + 80 °C
- Dimensions (LxWxH): 165x115x29 mm
- Weight: approx. 528 g
- Vibration resitant: > 5G

Camera

- 1/3“ CCD shutter color-camera
- 6 IR LED residual light amplifiers for better performance in dark areas (max. 3 m)
- Minimum illumination: < 0 lux
- Resolution: 470.000 pixel; 530 TV-lines
- Viewing angle: 130°
- Protection class: IP69
- Power supply: 12 V
- Power consumption: max. 3 W
- Vibration resistant up to 7 G
- Signal/noise ratio: 44 dB
- Operating temperature range: -30 °C to +80 °C
- Dimensions (WxHxD): 110x85x75 mm
- Weight: 390 g
- 20 m connection cable 394 IP (with waterproof WPA plug, AXION DIN 6 PIN)

EAN CRV 6002 set **40 41044 150685**

EAN DBC 114065S1 **40 41044 220692**
EAN CRV 5605M (monitor) **40 41044 220777**

Version: 1040614

Technische Änderungen und Irrtümer vorbehalten.

Axion AG Röntgenstraße 4 D-89264 Weißenhorn PHONE: +49 (0) 7309 / 42 88-0 info@axionag.de WWW.AXIONAG.DE