



CRV 7044 AIR Set

Digital wireless set

7" TFT LCD monitor for up to 4 wireless cameras



CRV 7044M AIR



DBC 114046AIR

WEITERE INFOS



Features:

- Radio set consisting of:
7" (17,78 cm) LCD-TFT monitor, rear view color-camera
incl. monitor stand
- Easy to install (only power supply)
- For 12 V & 24 V application
- Basic set with 1 camera

Monitor:

- Radio rear view monitor
- Digital connection for up to 4 cameras
- High resolution
- Quad-function for simultaneous display of 4 cameras


Rear view camera:

- Sturdy radio color-camera
- Camera viewing angle 120°
- Camera protection class IP69K
- 0,1 lux (day), 0 Lux (with IR)

Special accessories (optional)

- external antenna DANT 303
- Additional/spare camera DBC 114046 AIR

Technische Änderungen und Irrtümer vorbehalten.



CRV 7044 AIR Set

Digital wireless set

7" TFT LCD monitor for up to 4 wireless cameras



Technical data:

Monitor:

LCD size:	7"
Resolution:	800x3(RGB)x480
Contrast:	500:1
Brightness:	400 cd/m ²
Viewing angle:	U: 50° / D: 70°, R/L: 70°
Image ratio:	16:9
Channels:	4
Operating frequency range:	2400-2483,5 MHz
Transmission distance:	120 meters
Reception sensitivity:	-89 dBm
Data compression:	MPEG4
Transmission frequency:	17 dBm
Modulation:	2,4 G FSK/GFSK
TV system:	PAL/NTSC
Time delay:	ca. 120 ms
Power consumption:	max. 6 W
Speaker:	1,5 W / 8 Ω
Operating temperature:	-20°C~+70°C, RH 90%
Storage temperature:	-30°C~+80°C, RH 90%
Dimensions (WxHxD):	183 x 122 x 40 mm

Camera:

Sensor:	¼" CMOS OV7725
TV-system:	PAL/NTSC
Array-size:	640x480
Range:	3.984 mm (H) x 2.952 mm (V)
Scan modus:	Progressive
Sync. system:	Internal
Resolution:	420 TV lines
Operating temp.:	-20°C~+60°C, RH 90% Max.
Storage temp.:	-30°C~+80°C, RH 90% Max.
Min. illumination:	0,1 lux (day), 0 Lux (with IR)
Microphone:	Yes, built-in
elec. exposure:	up to 510:1
AGC:	Auto
S/N Ratio:	better than 48 dB
White balance:	Auto
BLC:	Auto
Power consumption:	max. 400 mA
Operating frequency range:	2400-2483,5 MHz
Transmission distance:	120 meters
Transmission performance:	17 dBm
Data compression:	MPEG4
Transmission speed:	12Mbps
Dimensions (WxHxD):	87 x 73 x 65 mm

EAN CRV 7044 AIR Set **40 41044 221033**

EAN DBC 114046AIR **40 41044 221040**

EAN CRV 7044M AIR (monitor) **40 41044 221064**