



# CRV 7005M

## Rear view monitor

7" LCD-TFT monitor for camera systems



WEITERE INFOS



Design made in Germany!

### Features:

- 7" (17,8 cm) rear view monitor with 2 camera inputs
- Easy to install and stock (plug & play)
- For 12 V & 24 V application
- 7 languages OSD
- 2 individual trigger wires
- Guide-lines engageable
- Buttons dimmable
- Power on at voltage
- Built-in speakers
- Priority adjustable
- Incl. monitor stand

Technische Änderungen und Irrtümer vorbehalten.



# CRV 7005M

## Rear view monitor

7" LCD-TFT monitor for camera systems



### Technical data:

- 7" TFT LCD monitor: 16:9
- Wide viewing angle: r/l 80°, u/d 40/60°
- High brightness: 350 cd/m<sup>2</sup>
- Resolution: 336.960 pixels
- Mirror/normal switch
- Day/night sensor
- Built-in speakers
- Video system: PAL/NTSC (auto)
- Power supply: 12/24 V (+/- 10%)
- Power consumption: < 7 W
- Operating temperature range: -20 °C to + 70 °C
- Storage temperature range: -30 °C to + 80 °C
- Dimensions (LxWxH): 200x115x29 mm
- Weight: approx. 400 g

EAN 40 41044 220784