

X-VISION

OPTIMA 8

Voltage Käyttöjännite Spänning Kasutuspinge	LED	Input voltage Tulojännite Inspänning Sisendpinge	Approvals Hyväksynnät Godkännande Sertifikaadid	Effective lumens Todellinen valoteho Testat ljusöde Testitud valgustugevus	Raw lumens Teoreettinen valoteho Teoretisk ljusöde Teoreetiline valgustugevus
9-33V	Osram LED	12V 5A, 24V 2.6A	R112, R10	4200lm	7000lm

Light temperature Värlämpötila Färgstemperatur Valgussoojus	IP class Suojaluokka Fuktskydd Niiskusklass	Ref.	Lens Linssi Lins Klaas	Body Runko Lamphus Korpus	Bracket Kinnitysjalusta Montagefäste Kinnistusjalg
5000K	IP69K	40	Polycarbonate Polykarbonaattia Polykarbonat Polükarbonaat	Aluminium Alumiinia Aluminium Alumiinium	Stainless steel Ruostumatonta terästä Rostfritt stål Roostevabast terasest



OPTIMA 8

9-33V OSRAM LED 12V 5A 24V 2.6A 4200LM (effective) 7000LM (theoretical) 5000K IP69K E9 40 ECE R112 E9 EMC ECE R10

